



MOTOR VEHICLE LUBRICANT OILS.

CEPSA GENUINE 25W50 HIGH MILEAGE 🖨 🚍

DESCRIPTION

High-performance lubricant formulated with Premium bases, designed to combat the effects of ageing on engines with over 100,000 km on the clock, with additives that help prevent oil leaks caused by engine wear, thus prolonging the engine's life.

PRODUCT APPLICATIONS

- High performance oil recommended for all types of light and heavy-duty vehicles, especially those with high mileage, in normal or heavy service (in urban or demanding motorway driving).
- Suitable for vehicles with a high oil consumption due to high mileage.
- Suitable for turbocharged or naturally aspirated vehicles especially overloaded by high temperatures.
- Recommended for either gasoline or diesel engines without particulate filters.

PRODUCT USES

- Its high viscosity and extremely low volatility permits reduced levels of oil consumption caused by wear of the engine's moving parts, maintaining a protective film even in the toughest conditions.
- It exceeds the protection requirements of all petrol and diesel engines that recommend an API SL/CF or lower category.
- It has a high detergent and dispersant power, preventing the formation of deposits in the crankcase and pistons, and lacquers or varnishes in the motor sleeves.
- Excellent oxidation (thickening) and thermal stability, meaning the oil can withstand many kilometres at high crankcase temperatures (150°C) without deteriorating.

SPECIFICATIONS

API SL/CF

TYPICAL CHARACTERISTICS

| CHARACTERISTIC | UNITS | METHOD | GENUINE HIGH MILEAGE |
|-------------------------|----------|-------------|----------------------|
| SAE Grade | - | - | 25W-50 |
| Density at 15°C | g/ml | ASTM D 4052 | 0.898 |
| Viscosity at 100°C | cSt | ASTM D 445 | 20,3 |
| Viscosity at 40°C | cSt | ASTM D 445 | 202 |
| Viscosity index | - | ASTM D 2270 | 117 |
| CCS viscosity at -10°C | сР | ASTM D 5293 | 6386 |
| Freezing point | °C | ASTM D 5950 | -30 |
| Flash point, V/A | °C | ASTM D 92 | 240 |
| Base number, TBN | mg KOH/g | ASTM D 2896 | 10.7 |
| Sulphated ash | % (m/m) | ASTM D 874 | 1.4 |
| HTHS viscosity at 150°C | сР | ASTM D 4683 | 5,0 |

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product in accordance with the applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.