

ERTOIL HIKE ATF

DESCRIPTION



Synthetic oils for automatic transmissions. This oil allows longer drain intervals even under the most severe conditions.

Applications

- Indicated for use in professional transport ambits.
- Recommended for its use in transmissions under severe conditions.
- Miscible with traditional ATF products.
- Also suitable for servo-transmissions and industrial hydraulic systems.
- For all weather conditions and types of driving.

Product features

- Exceptional transmission system cleaning.
- Significant wear reduction, extending component life.
- Its friction properties allow smooth gearbox changes, and the oil retains these properties for an extended period.
- Excellent performance at high temperatures.
- Fast circulation and outstanding lubrication at very low temperatures.
- High foam formation control.
- Highly resistant to thermal degradation and oxidation.

QUALITY LEVELS

- G. Motors DIII-H
- Allison TES-295
- Ford MERCON V
- Allison C-4
- VOLVO 97341

TYPICAL CHARACTERISTICS

SPECIFICATION	UNITS	METHOD	ERTOIL HIKE ATF
Density at 15°C	kg/l	ASTM D 4052	0.847
Flash point, V/A	°C	ASTM D 92	>200
Freezing point	°C	ASTM D 5949	-42
Viscosity at 100°C	cSt	ASTM D 445	7.15
Viscosity at 40°C	cSt	ASTM D 445	33.7
Viscosity index		ASTM D 2270	183
Brookfield viscosity -40°C	cP	ASTM D 2983	<20000
Colour		ASTM D 1500	Red

ENVIRONMENT, HEALTH and SAFETY

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.