



CEPSA CHAMPU

AUTOMATIC AND MANUAL WASH

CEPSA CHAMPU is formulated with the most modern surfactants, corrosion inhibitors and special products that allow its use with water of any hardness.

It has high foaming power, easing its use at low concentrations.

Its excellent lubricating power lengthens the life of brushes in car-wash tunnels and bridges.

DOSAGE

Automatic washing:

Introduce the pure product by means of a venture or dosage pump, adjusting both so that the outlet concentration at the nozzles is about 1-2 %

Manual washing:

Dilute with water to an approximate concentration of 1- 3 %

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

TYPICAL CHARACTERISTICS

CEPSA CHAMPU	
Appearance	Brown transparent liquid
Odour	Odour free
pH concentrate	8.00
pH at 1%	8.00
Density a 20°C	1.043
Ionic character	Anionic
Freezing point °C	-1.0
Active ingredients, %	13.5

The values of typical characteristics appearing in the table are given for guidance purposes and do not constitute a guarantee. These values may be modified without prior notice.

CEPSA Lubricantes S.A. - C/ Ribera del Loira, 50 - 28042 Madrid - www.cepsa.com/lubricantes-eng

Rev. 2, Month: January, Year: 2005