



GREASES FOR INDUSTRIAL USE

CEPSA ARGA CALCIO 2 PLUS 🖨 🛁

DESCRIPTION

PRODUCT APPLICATIONS

• Multipurpose anhydrous calcium soap grease for moderate automotive, marine and industrial use, in a wide temperature range (-20° C to 100° C).

• Specially indicated for general lubrication of mechanisms exposed to the action of water, being resistant even to saline environments.

• Protection of metal surfaces against rust and corrosion.

PRODUCT PERFORMANCE

• Grease made with mineral oil and anhydrous calcium soap.

• With the necessary additives to provide good corrosion protection and great stability to oxidation at temperatures not higher than recommended.

- Easily injectable and pumpable.
- Presents excellent adhesiveness and envelopment capacity.
- Totally insoluble and water resistant.
- Compatible with greases of the same nature.

SPECIFICATIONS

DIN 51502: K2G-20
ISO 3743-9: L-XBBHA2

TYPICAL CHARACTERISTICS

CHARACTERISTICS	UNITS	METHOD	CEPSA ARGA CALCIO 2 PLUS
Colour		Visual	Light Yellow
Nlgi Consistency		D-217	2
Soap-Like			Anhydrous Calcium
Drop Point	°C	D-566	>145
Application Temperature	°C		-20 To 100
Base Oil			Mineral
Viscosity At 40°C	Cst	D-445	68
Penetration At 60 Hits	0.1 Mm	D-217	265-295
Copper corrosion (24 h/100°c) max.		D-4048	1
Corrosion Protection		D-1743	Pass

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.