

LUBRICANTS FOR MOTORSAWS

CEPSA H-150 ESPECIAL MOTOSIERRAS

DESCRIPTION

A lubricant oil formulated with highly-refined paraffinic base oils and additives that provides the product high protection with EXCELLENT ADHERENCE to the surface to be lubricated.

PRODUCT APPLICATIONS

- Specially recommended for the lubrication of motor-saws.

PRODUCT PERFORMANCE

- High viscosity index.
- Reduction of oil loss.
- Excellent surface adhesion.
- Reduction of oil consumption.
- High resistance to oxidation.
- Prevents metal wear.

SPECIFICATIONS

- DIN 51501 L-AN
- ISO 6743/1 L-AN
- ISO 6743/4 HL

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	ASTM STANDARD	CEPSA H-150 ESPECIAL MOTOSIERRAS
Density 15 °C	Kg/l	ASTM D-4052	0,884
Flash Point, COC	°C	ASTM D-92	240
Pour Point	°C	ASTM D-5950	-30
Viscosity at 100 °C	cSt	ASTM D-445	18
Viscosity at 40 °C	cSt	ASTM D-445	150
Viscosity Index	-	ASTM D-2270	129

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.