

MOTORCYCLE LUBRICANTS

CEPSA MOTO 2T URBAN PRO 

DESCRIPTION

A unique synthetic lubricant for the new generation of motorcycles and mopeds, specially developed with smokeless technology for urban driving cycles.

PRODUCT APPLICATIONS

- Provides exceptional performance in urban traffic, where the lubricant oil must operate under continual stop/start conditions.
- Particularly recommended in places and regions requiring low smoke emissions, such as urban areas and special environmental protection sites, etc.
- Compatible with all types of petrol, it should be used as a 2% premix or at the dose recommended by the manufacturer. Can also be used in oil-injection or self-mix systems.

PRODUCT PERFORMANCE

- A high-quality oil that exceeds JASO FC/ISO L-EGC requirements in terms of detergency, lubricity, low deposit formation in the piston and no smoke.
- Its unique concentration of synthetic bases extends the life of the engine (preventing seizure) with respect to mineral oils with JASO FB/ISO L-EGC and API TC mineral quality.
- Low-ash additive technology with excellent dispersant capacity, which prevents deposits from forming in the ports and extends the lifespan of the spark plugs without fouling.

SPECIFICATIONS

- JASO FC
- ISO L-EGC
- API TC
- TISI 1040-2541



CUMPLE JASO M 345
CALIDAD FC GARANTIZADA POR:
CEPSA Comercial Petróleo S.A.U

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA MOTO 2T URBAN PRO
Density at 15°C	g/ml	ASTM D4052	0.867
P/M Flash Point	°C	ASTM D93	76
Pour Point	°C	ASTM D5950	-24
Viscosity at 100°C	cSt	ASTM D445	8.65
Viscosity Index	-	ASTM D2270	143
Total Base Number (TBN)	mg KOH/g	ASTM D2896	1.2
Color:	-	ASTM D1500	Red

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.