

# ERTOIL HIKE 15W40

## DESCRIPTION



Multi-grade oil especially designed to exceed the API SL specification, meeting the requirements for use in all types of petrol and diesel engines: compact and saloon cars, MPVs, etc.

### Applications

- Designed for use in the engines of the major vehicle manufacturers, including cars, vans and light trucks.
- For petrol engines with turbochargers, direct injection, common-rail, intercooler, etc. and traditional diesel technologies (indirect injection).
- For all weather conditions and types of driving.

### Product features

- Suitable for all seasons of the year, this oil guarantees the whole engine is well lubricated on start up, even at low temperatures.
- It reduces the friction between metallic parts, avoiding potential engine wear or seizing.
- It has a high detergent/dispersant power, stopping sludge and dirt from building up in the engine, keeping it clean and protected.

## QUALITY LEVELS

- API SL

## TYPICAL CHARACTERISTICS

SPECIFICATION	UNITS	METHOD	ERTOIL HIKE 15W40
<b>SAE Grade</b>	-	-	<b>15W40</b>
Density at 15°C	g/ml	ASTM D 4052	0,884
Viscosity at 100°C	cSt	ASTM D 445	14,4
Viscosity at 40°C	cSt	ASTM D 445	107
Viscosity index	-	ASTM D 2270	137
CCS Viscosity at -20°C	cP	ASTM D 5293	5616
Freezing point	°C	ASTM D 5949	-33
Flash point, COC	°C	ASTM D 92	228
Base number, TBN	mg KOH/g	ASTM D 2896	7,6
Sulphated ash	% (m/m)	ASTM D 874	1,01
HTHS viscosity at 150°C	cP	ASTM D 4683	4,15

## ENVIRONMENT, HEALTH and SAFETY

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee.

These values may be modified without any prior warning.