

# ERTOIL HIKE ATF

## DESCRIPTION



Lubricating oil manufactured with specially selected bases and a powerful additive package for use in transmissions requiring General Motors DIII specification.

### Product applications

- Automatic transmissions at General Motors DIII level
- Recommended for use in transmissions operating under severe conditions.
- Automatic transmissions in passenger cars and heavy-duty vehicles.
- Also suitable for use in servo transmissions and industrial hydraulic systems.

### Product performance

- Exceptional cleanliness of the transmission system.
- Maximum protection of planetary gears and torque converter
- Excellent protection of all parts of automatic transmissions, torque converters, gearboxes and hydraulic circuits.
- High resistance to foaming tendency.
- High oxidation stability and resistance to thermal degradation

## SPECIFICATIONS

- G. Motors DIII
- MB 236.9
- Allison C-4
- VOITH 55.6335.xx
- MAN 339 V1/Z1

## TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	ERTOIL HIKE ATF
Density at 15°C	kg/l	ASTM D 4052	0.860
V/A flash point	°C	ASTM D 92	>200
Pour Point	°C	ASTM D 5949	-39
Viscosity at 100°C	cSt	ASTM D 445	7.7
Viscosity at 40°C	cSt	ASTM D 445	38.2
Viscosity Index		ASTM D 2270	183
Brookfield viscosity -40°C	cP	ASTM D 2983	<50000
Color		ASTM D 1500	Red

## HEALTH & SAFETY and ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.